

Technical Data Sheet



ULTRA GUARD SAE 40 SJ/CF-4 High Quality Monograde Lubricant

PRODUCT INFORMATION

Single grade oil for gasoline & diesel engines operating under extreme conditions. It offers advanced protection against engine wear, reduces deposits in the combustion chamber, and maintains peak engine performance, even in the toughest operating conditions.

ULTRA GUARD SAE 40 is a cost-effective oil for the lubrication of medium-duty gasoline and diesel engines. Due to its low ash content, thermal stability, enhanced anticorrosion and antirust additives they do not form hard deposits thus keeping engine parts protected against sludge. They may be used as top-up in both gasoline and diesel engines. Please ensure product specifications match vehicle requirements before use.

PERFORMANCE LEVEL

SAE 40, API SJ/CF-4, ACEA E2, A2/B2

Technical Properties

Test	Method	Typical Values
Appearance	Visual	Clear and Bright
Density @ 15 °C, g/cm ³	ASTM D 4052	0.8891
Kinematic Viscosity (cSt) 40°C	ASTM D445	142.5
Kinematic Viscosity (cSt) 100°C	ASTM D445	14.47
Viscosity Index	ASTM D2270	97
Pour Point, °C	ASTM D97	-24

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all our customers

The specifications above are typical but, may be changed without notice, always consult owner's manual before use. Values are indicative of standard test values and may change in line with industry norms. No warrantee is expressed or implied.
Produced on behalf of Star Oil Ltd by Mactex Oil Distribution Ltd, Ireland.

